

## **Converting Machine Capabilities**

June 12, 2023

	REWINDING / SLITTING											
Machine	Туре			l Informat	ion			Rewin	d Informa	Typical Material Types/Notes		
		Width	OD	Driven	Number Of Unwinds	Cores	Minimum Slit Width	OD	Cut Type	Plying	Cores	
Jagenburg	2 - Drum Surface	133"	90" / 3 Ton	Yes - Belt	2	3", 6", 6.5", 6.75", 8", 10", 10.5", 12", 16" / Others can be made	3"	59"	Shear / Score	2 Webs	Same as Incoming	Light Weight Tissue, Toweling, MG Stock, Airlaids, DRC, TAD, Spunbond, Spunlace, Meltblown, Etc.
PTP	2 - Drum Surface	110"	90" / 3 Ton	Yes - Belt	2	3", 6", 6.5", 6.75", 8", 10" 12", 16" / Others can be made	3"	60"	Shear	2 Webs	Same as Incoming	Light Weight Tissue, Toweling, MG Stock, Airlaids, DRC, TAD, Spunbond, Spunlace, Meltblown, Etc.
ARROW	Center/Surface	83"	72" / 3 Ton	Yes - Belt	1	3", 6", 6.5", 6.75", 8", 10" 12", 16" / Others can be made	2"	60"	Shear	No	3", 6"	Light Weight Tissue, Toweling, MG Stock, Core Stock, Airlaids, DRC, TAD, Spunbond, Spunlace, Meltblown, Etc.
JOTA	Center/Surface	128"	90"/3 Ton	Yes - Belt		3", 6", 6.5", 6.75", 8", 10", 10.5", 12", 16" / Others can be made	3"	60"	Shear / Score	2 Webs	Same as Incoming	Light Weight Tissue, Toweling, MG Stock, Airlaids, DRC, TAD, Spunbond, Spunlace, Meltblown, Etc.
ACM	2 - Drum Surface Small Rolls	130"	60"/2.5 Ton	Yes - Belt	1	3", 6", 6.75"	2"	20"	Shear	No	Coreless, 3"	Toweling, Meltblown, DRC, Airlaid, Spunlace, TAD, Etc. Perforation Capability from 90 mm to 400 mm.

	PLY BONDING / LAMINATIONS & AQUEOUS COATING (Water Based Adhesive)											
Machine	Туре			Unwind	Informat	ion			Rewin	d Informa	Material Types	
		Width	OD	Driven	Number Of Unwinds	Cores	Minimum Slit Width	OD	Cut Type	Plying	Cores	
3DL	3 - Ply Laminator With Embossing		60"	Yes - Belt	3	3", 6", 6.75"	6"	48"	Shear	3 webs	3", 6"	Tissue, Toweling, Netting, Airlaid, Spunbond, Etc.
PTP	2 - Drum Surface	108"	90" / 3 Ton	Yes - Belt		3", 6", 6.5", 6.75", 8", 10" 12", 16" / Others can be made	3"	60"	Shear	2 Webs		Light Weight Tissue, Toweling, MG Stock, Airlaids, DRC, TAD, Spunbond, Spunlace, Meltblown, Etc.

	LAMINATIONS - HOT MELT ADHESIVE											
Machine	Туре	Unwind Information							Rewin	d Informa	Material Types	
		Width	OD	Driven	Number Of Unwinds	Cores	Minimum Slit Width	OD	Cut Type	Plying	Cores	
Jagenburg	2 - Drum Surface	124"	90" / 3 Ton	Yes - Belt	2	3", 6", 6.5", 6.75", 8", 10" 12", 16" / Others can be made	3"	59"	Shear	Yes		Tissue, Toweling, MG Stock, Core Stock, Airlaids, DRC, TAD, Needlepunch, Spunbond, Spunlace, Meltblown, Films

	FOLDING												
Machine	Flat Sheet Width		Flat Sheet Length		Roll OD	Fold Type	Production Notes	Embossing	Material Types				
	Min.	Max	Min.	Max									
HS-17	6"	20"	16.75"	16.75"	55"	1/4 fold, 6 fold, 8 fold			Tissue, Toweling, Scrim Tissue, Airlaids, DRC, TAD, Spunbond, Spunlace, Meltblown				
CMD # 202	8"	65"	48"	*Note	28"	Folded to Roll (Coreless)	*NOTE: Maximum length is determined by material caliper		Laminations, Films, DRC, Airlaid, Spunbond, meltblown				
CMD # 204	8"	65"	48"	*Note	28"	Folded to Roll (Core or Coreless)	*NOTE: Maximum length is determined by material caliper		Laminations, Films, DRC, Airlaid, Spunbond, meltblown				